

FOL 919-950 – MASKING TAPE 100°C

Description

Masking tape for wall-painting on building sites

Product data

Backing:	59 g/m ² natural white saturated crepe paper
Adhesive:	natural rubber and resins solvent based
Total thickness:	0.125 mm
Adhesion to steel:	4.8 N/25mm
Tensile strength MD:	87.5 N/25mm
Elongation at break:	8%
Temp. resistance:	80°C (30 min.)

Application

Masking tape suitable for wall-painting on building and construction sites, industrial and car repair applications when temperature does not exceed 80°C.

Features

Natural rubber and resins solvent based adhesive

Saturated paper backing

Benefits

- good adhesion even on irregular surfaces
- heat resistant up to 80°C (30 minutes)
- easy removal without adhesive residue, if removed as soon as paint is dry
- well conformable to most shaped surfaces
- compatible with most common paints and lacquers
- removable without breaking
- hand tearable

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature 23°C, out of direct sunlight, 50% relative humidity. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.